MADE IN INDIA

RUBBER KING™
RELIABILITY MEANS EVERYTHING!

PREMIUM
RESILIENT SOLID TYRES
Developed & Manufactured by Rubber King Tyre Pvt. Ltd.

RUBBER KING
RELIABILITY MEANS EVERYTHING!

RUBBER KING TYRE PRIVATE LIMITED

Item No	Tyre Size	Tyre Size (Metric Equivalent)	RIM SIZE
1	4.00-8	-	3.00D-8
2	5.00-8	-	3.00D-8
3	15x4 1/2-8	125/75-8	3.00D-8
4	16x6-8	150/75-8	4.33R-8
5	18x7-8	180/70-8	4.33R-8
6	6.00-9	-	4.00E-09
7	21x8-9	200/75-9	6.00E-09
8	6.50-10	-	5.00F-10
9	6.50-10	-	5.50F-10
10	23x9-10	225/75-10	6.50F-10
11	7.00-12	-	5.00S-12
12	27x10-12	250/75-12	8.00G-12
13	5.50-15	`-	4.50E-15SDC
14	7.00-15	-	5.50-15
15	7.50-15	-	5.50-15
16	7.50-15	-	6.00-15
17	7.50-15	-	6.50-15
18	8.15-15 (or) 28x9-15	225/75-15	7.00-15
19	8.25-15	-	6.50-15
20	250-15	250/70-15	7.00-15
21	300-15	315/70-15	8.00-15
22	140/55-9	-	4.00E-09
23	200/50-10	-	6.5F-10
24	23x10-12	250/60-12	8.00G-12
25	28x12.5-15	355/45-15	9.75-15
26	7.50-16	-	5.50-16
27	7.50-16	-	6.00-16
28	9.00-20	-	6.50-20
29	9.00-20	-	7.00-20
30	10.00-20	-	7.50-20
31	10.00-20	-	8.00-20
32	11.00-20	-	7.50-20
33	11.00-20	-	8.00-20

Technical Description

- Three stage Solid Resilient Tyre for improved ride comfort and reduced down time.
- Suitable for wide range of Forklifts & other material handling equipments.
- Heat Resistant, Cut & chip resitant, Oil resistant, Non marking & LOC variants are available based on Customer Specific Requirement.
- Ultra Premium variant available for continuous operation(3 shift operation)
- Check rim for size & max load beofore tyre fitment, Wheel load is lower of the load capacity of rim or tyre.
- The speeds stated are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.

* Images displayed are for representation purpose and actual product may differ.